



Waterproofing

SuperPatch

Off White and Concrete

7 lb. Pail, 15 lb. Pail and 70 lb. ProPack



DAMTITE WATERPROOFING

733 E. Main Street
 Monongahela, PA 15063-1499
 1-800-223-8483
 1-724-258-7175
 Fax: 724-258-3188
 e-mail: info@damtitewaterproofing.com
 website: www.damtitewaterproofing.com

- Adheres to concrete, glass, wood & metal
- Repairs cracks or holes
- Resurfaces walks, driveways & walls
- Anchors bolts and railings into concrete

Description:

Damtite SuperPatch is a two-component, multipurpose, waterproofing patch compound for repairing or resurfacing concrete, masonry, stucco and brick, up to 1 inch thickness in one application. Just mix the powder with the bonding liquid in the pail. It is a non-shrink formula with exceptional strength and adhesion for use on worn concrete/masonry as well as glass, steel, aluminum and wood. Can be featheredged or applied to desired thickness, eliminating multiple layers. Ideal to anchor bolts, railings, and other fixtures into concrete, and to build up worn or broken step corners without using forms. Use for vertical/horizontal, above or below grade patch and repair projects both inside and out. Will not cause acidic reaction with aluminum. Available in two colors: concrete and off-white.

Application Guidelines:

Damtite SuperPatch can be applied with trowel or putty knife. Wear protective gloves and goggles. Product's superior adhesion eliminates the need to widen cracks with chisel prior to application.

Surface Preparation:

Surface must be structurally sound and clean for best adhesion. Clean surface thoroughly using a wire brush or chisel to remove any loose mortar, paint, dirt, grease, or oil. Remove any white, salt-like deposits (efflorescence) with *Damtite Concrete Cleaner* or mild acid. Rinse surface with water and remove any standing water. Dampen surface with clean water prior to applying for best adhesion.

Mixing:

Using clean container, first add quart of bonding liquid; do not dilute. Then, gradually add all powder while stirring, until all material is mixed to thick paste. A paint stirrer attachment for electric drill is recommended when mixing large quantity. If mixture becomes too thick to work, add small amount of clean water, since too much water may cause cracking. When mixing smaller quantities, add 3 1/3 parts powder to 1 part bonding liquid.

Application:

For repairing cracks:

Force mixture into cracks with putty knife or trowel. Fill cracks completely and level with surrounding surface. When replacing loose mortar, work mixture into surface and smooth with point of trowel. **For leveling floors:** trowel mixture onto worn sections and level with surrounding area. Allow to dry 48 hours before subject to traffic. **For featheredging:** brush edge of patch with a paint brush, moistened with water.

Clean trowel frequently during application. Use little pressure when smoothing patch. Try not to tear skin of patch since top surface will harden rapidly. Product can be worked for 20-30 minutes after mixing, depending upon temperature and humidity, but surface skin may set sooner. Sets in 4 hours, but allow 48 hours for complete cure. If painted finish desired, use latex base paint after 48 hours.

Container/Coverage:

7 lb unit:

Contains 6 lbs powder & 1 pint Bonding Liquid
 6 lbs covers about 3 sq. ft., 1/4 inch thick (110 cubic inches).

15 lb unit:

Contains 12 lbs powder & 1 qt. Bonding Liquid
 12 lbs covers about 6 sq. ft., 1/4 inch thick (220 cubic inches).

70 lb unit:

Contains 50 lbs powder & 1 gal. Bonding Liquid
 50 lbs covers about 25 sq. ft., 1/4 inch thick (0.05 cubic feet).

Clean-Up/Storage/Disposal:

Wash hands and tools with soap and water immediately after use. Store unused powder tightly sealed in original container. Protect from freezing. Dispose of product in accordance with local, state, and federal requirements.

Read Material Safety Data Sheet (MSDS) before using this product.

Limited Warranty:

Manufactured according to quality control standards. Warranted free of manufacturing defects. If defective, return to place of purchase, and, with proof of purchase, Damtite Waterproofing will replace product of equal value at no additional charge. This warranty is in place of any implied warranty of merchantability and all other warranties, expressed or implied.

CAUTION:

Keep Out of Reach of Children

Contains Portland Cement, Silica and Lime. It may cause skin burns and/or allergic reactions or be irritating to eyes and skin. Wear protective gloves and goggles. For prolonged professional use, avoid breathing dust by wearing NIOSH/MSHA-approved respirator and by mixing in area with adequate ventilation. In case of eye contact, flush area with clean water immediately and call a doctor or poison control center. Do not take internally. If ingested, take 1-2 glasses of water and call doctor immediately.

Available in 2 colors: concrete and off-white.
 Coverage: one pound fills 18 cubic inches, 1/4 inch thick

Size	Color	Stock No.	Pack
7 lb. Pail	Off White	04071	6
7 lb. Pail	Concrete	04072	6
15 lb. Pail	Off White	04151	4
15 lb. Pail	Concrete	04152	4
70 lb. Pail ProPack	Off White	04701	1
70 lb. Pail ProPack	Concrete	04702	1

DAMTITE WATERPROOFING
 May 2010
 Waterproofing SuperPatch - 7 lb. Pail, 15 lb. Pail & 70 lb. ProPack