

pakmix®

QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE

Description:

PAKMIX® Surface Bonding Cement is a blend of cementitious material, fiberglass fibers and proprietary ingredients.

Suggested Uses:

- ▶ Insulation Board Coating.
- ▶ Dry Stacked Block Construction.
- ▶ Decorative Coatings.
- ▶ Patching Masonry & Stucco.

Preparation:

All surfaces should be clean and free of foreign substances that would cause poor bonding. The surface to be coated should be moistened before applying PAKMIX® Surface Bonding Cement.

Directions for Mixing:

Pour entire bag of PAKMIX® Surface Bonding Cement into a clean container. Add clean water to achieve a mortar-like consistency. Mix one to two (1-2) minutes. Avoid mixing in excess of five (5) minutes or fibers will break down.

Items you may need:

- ▶ Safety Glasses
- ▶ Rubber Gloves
- ▶ Mortar Box or Wheelbarrow
- ▶ Trowel
- ▶ Shovel or Hoe

Packaging & Yields:

Packaged in 50 lb. bags and will cover 50 sq. ft. x 1/8" thick.

For Best Results:

Use only when the temperature is 40° F or higher. In cold weather use warm water. Only apply on clean, damp surface. As with all cement products, keep moist for at least three (3) days by an occasional fine misting with water.

Clean Up:

Clean up is simple and easy with soap and water. Clean tools before material hardens.


Caution:

INJURIOUS TO EYES AND CAUSES SKIN IRRITATION. This product contains Portland cement (CAS #65997-15-1). When Portland cement is combined with water, an alkali mixture is created. Contact with an alkali mixture can cause severe burns. Protect against potential injury by: avoiding contact with wet cement; by wearing eye protection; and by wearing clothing on your hands, feet, and body that are waterproof. If the freshly mixed cement should contact skin or eye(s), immediately flush with water for a minimum of 15 minutes. If symptoms continue, consult a physician immediately. Keep out of reach of children.

HARMFUL IF INHALED. This product contains Free Silica (CAS #14808-60-7). When Free Silica is inhaled, it may cause delayed respiratory and other health problems. Free Silica has been listed by I.A.R.C. as a possible carcinogen based upon laboratory animal test data and limited evidence of human carcinogenicity. Avoid breathing cement dust. Keep the bag closed when not in use, and use only in well ventilated areas. Follow OSHA Safety and Health Standards for crystalline silica. If this product must be used in an enclosed area, use a NIOSH approved dust respirator.

Keep Out of Reach of Children:

Material safety data sheet available upon request.



SURFACE BONDING CEMENT
PRO LINE

pakmix®

605 Industrial Way, Dixon, California 95620
(800) 272-5649 • FAX (707) 693-9349
www.pakmix.com

SURFACE BONDING CEMENT